




INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Dagger-Deck™ Screws • Square Bugle Coarse • Tan ACQ Dagger Ultra-Guard Coating™

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Head	Thread	Point
6 x 1	9	10,000	ACQDK06100TAN	#2	Bugle	Single Lead	Pierce
6 x 1-1/4	9	8,000	ACQDK061104TAN	#2	Bugle	Single Lead	Pierce
6 x 1-5/8	9	5,000	ACQDK06158TAN	#2	Bugle	Single Lead	Pierce
6 x 2	9	3,500	ACQDK06200TAN	#2	Bugle	Single Lead	Pierce
8 x 2-1/2	8	2,500	ACQDK08212TAN	#2	Bugle	Single Lead	Pierce
8 x 3	8	2,000	ACQDK08300TAN	#2	Bugle	Single Lead	Pierce
10 x 3-1/2	8	1,500	ACQDK10312TAN	#2	Bugle	Single Lead	Pierce
10 x 4	8	1,000	ACQDK1040TAN	#2	Bugle	Single Lead	Pierce

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Dagger Ultra-Guard Coating™ is a zinc/chromate substrate with proprietary organic topcoat, multi step process for use with any ACQ treated lumber which provides 1000 hour salt spray corrosion resistance
<i>application:</i>	wood to wood in exterior applications.
<i>installation:</i>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

Meets or exceeds the following specifications:

ASME B 18.6.1	Standard Specification for Wood Screws
ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
ASTM C1002	Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs
ASTM F1941	Specification for Electrodeposited Coatings on Threaded Fasteners

Ultimate Value Chart

DIAMETER	2 x 4 Red Wood Pull Out	3/4 Particle Board Pull Out	2 x 4 Fir Pull Out	Minimum Torsional Strength (Lb)
#6	318	284	424	24
#8	518	290	540	39
#10	587	388	563	56

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes.
All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

ACQDK.21