## Cordless PROCCS+ Multi-Purpose Combo System



Sure-grip guide tube increases stability for a broad range of screws treads, sheathing, decks/docks, fiber-cement siding to steel

- Expanded depth settings for high-density flooring materials
- Reversible and replaceable non-skid teeth
- Sure-grip guide tube increases stability for a broad range of screws
- The patented curved collation strips (US Patent 7,051,875) hold the screws up and away from the work surface, making moving and positioning the tool easier. They are also pointed on the inserted end to simplify loading.

Limited lifetime warranty on attachment and extension, one-year limited warranty on screwdriver motors (see specific manufacturer's warranty for more information)



## The cordless PROCCS+ combo system includes:

- PRO300SG2 decking attachment (also sold separately)
- PRO200SG2 multipurpose attachment (also sold separately)
- · Lightweight G3 extension for stand-up driving
- DeWalt® 2,000 rpm 20V cordless driver motor
- Two lithium ion batteries and charger
- Screw quiver for keeping screws at your fingertips
- · Soft carrying case

Drive These Collated Screws				
1"-3"				
Strong-Drive® WSV Subfloor screw	p. 229	Bugle-Head Wood screw	p. 222	
Deck-Drive <sup>™</sup> DCU Composite screw	p. 226	WSC Wood screw	p. 234	
Deck-Drive DWP Wood SS screw	p. 219	WSFLRV Wood-to-CFS/Aluminum screw	p. 247	
Deck-Drive DHPD Hardwood Decking screw	p. 220	WSHL Subfloor screw	p. 231	
Deck-Drive DCSD Composite-to-Steel screw	p. 228	Strong-Drive PPHD Sheathing-to-CFS screw	p. 239	
Deck-Drive DSV Wood screw	p. 218	MTH Wood Underlayment screw	p. 232	
Trim-Head screw — Type-17 point	p. 222	CBSDQ Sheathing-to-CFS screw	p. 244	
Trim-Head screw — sharp point	p. 221			

System Options	Model No.
DeWalt 2,000 rpm cordless screwdriver motor	PROCCS+DC2K
Parts	Model No.
PR0300S attachment only	QDPR0300SG2
PR0200S attachment only	QDPR0200SG2
Replacement attachment mandrel	PMANDREL75
Replacement extension	QDEXTG2

For more information on screwdriver motors and RPM recommendations per application, see pp. 204–206.