


Collated Exterior Screws



Deck-Drive™ DSV WOOD Screw


Preservative-Treated Decking and Exterior Wood-to-Wood Applications

The Deck-Drive DSV Wood screw is a powerful fastening solution for preservative-treated decking applications. With its under-head nibs and fast-start tip, the DSV is ideally suited to be driven and countersunk into today's wood deck boards. The shank is designed to withstand the swelling and shrinkage that is common with fast-growth lumber. Available in hand-drive and in collated strips for use in our Quik Drive® auto-feed screw driving system, DSV screws are also offered in a variety of sizes to fasten fascia and trim.

Features:

- Low-torque threads
- Ribbed-head design countersinks easily and provides a clean, finished appearance
- High-low threads with Type-17 point provides fast starts
- Optimized threads for lumber
- Quik Guard® coating provides corrosion resistance for exterior and certain preservative-treated wood applications
- Meets the performance requirements of ICC-ES AC257 exposure conditions 1 and 3
- Colors to blend in with most woods
- This screw is also available in bulk for hand-drive installation; see p. 65 for details

Quik Guard Coating — Tan



Size	Length (in.)	500 ct. Model No.	750 ct. Model No.	1,000 ct. Model No.	1,500 ct. Model No.	2,000 ct. Model No.	PRO 300SG2	PRO 250G2	PRO 200SG2
# 8	1¼	—	—	—	—	DSVT114S			✓
# 8	1½	—	—	—	—	DSVT158S		✓	✓
#10	2	—	HCKDSVT2S	—	DSVT2S	—	✓	✓	✓
#10	2½	HCKDSVT212S	—	DSVT212S	—	—	✓	✓	
#10	3	—	—	DSVT3S	—	—	✓		




Quik Guard Coating — Red



Size	Length (in.)	1,000 ct. Model No.	1,500 ct. Model No.	2,000 ct. Model No.	PRO 300SG2	PRO 250G2	PRO 200SG2
#8	1¼	—	—	DSVR114S			✓
#8	1½	—	—	DSVR158S		✓	✓
#10	2	—	DSVR2S	—	✓	✓	✓
#10	2½	DSVR212S	—	—	✓	✓	
#10	3	DSVR3S	—	—	✓		



Quik Guard Coating — Gray



Size	Length (in.)	1,000 ct. Model No.	PRO 300SG2	PRO 250G2	PRO 200SG2
#10	2½	DSVG212S	✓	✓	
#10	3	DSVG3S	✓		

