



PIPE SIZE	ROD DIA. (D)	L	C	T	WT. PER C
1/2	1/4"-20	3 1/4"	15/16"	2 3/8"	8
3/4	1/4"-20	3 5/16"	1 1/8"	2 3/8"	8
1	1/4"-20	3 7/16"	1 3/8"	2 3/8"	9
1 1/4	3/8"-16	3 3/4"	1 11/16"	2 3/8"	23
1 1/2	3/8"-16	4"	2"	2 1/2"	25
2	3/8"-16	4 1/2"	2 7/16"	2 1/2"	28
2 1/2	1/2"-13	5 1/4"	2 15/16"	3"	58
3	1/2"-13	5 13/16"	3 9/16"	3"	64
3 1/2	1/2"-13	6 1/4"	4 1/16"	3"	70
4	1/2"-13	6 13/16"	4 9/16"	3"	75
5	1/2"-13	7 13/16"	5 5/8"	3"	87
6	5/8"-11	9 1/2"	6 3/4"	3 3/4"	163
8	5/8"-11	11 1/2"	8 3/4"	3 3/4"	201
10	3/4"-10	13 13/16"	10 7/8"	4"	365
12	7/8"-9	16 1/16"	12 7/8"	4 1/4"	562
14	7/8"-9	17 5/16"	14 1/8"	4 1/4"	619
16	7/8"-9	19 5/16"	16 1/8"	4 1/4"	677
18	1"-8	21 11/16"	18 1/8"	4 3/4"	1,040
20	1"-8	23 11/16"	20 1/8"	4 3/4"	1,130
24	1"-8	27 11/16"	24 1/8"	4 3/4"	1,330
28	1"-8	31 11/16"	28 1/8"	4 3/4"	1,520
30	1"-8	33 11/16"	30 1/8"	4 3/4"	1,620
36	1"-8	39 11/16"	36 1/8"	4 3/4"	1,900
42	1"-8	45 11/16"	42 1/8"	4 3/4"	2,194
48	1"-8	51 11/16"	48 1/8"	4 3/4"	2,485

AVAILABLE IN PLAIN, ZINC CLEAR, HOT DIP GALVANIZED, 304SS & 316SS

ITEMS ARE PITCH BODY UNDERSIZED WITH ROLLED THREADS

COMMERCIAL NUT FIT ** NOT UNC-2A FIT **

SOLD BULK NO NUTS UNLESS SPECIFICALLY QUOTED OTHERWISE

DIAMETERS 1/4"-20 THRU 5/8"-11 GENERALLY MADE FROM COLD DRAWN 1006-1018 COIL STEEL

DIAMETERS 3/4"-10 THRU 1"-8 GENERALLY MADE FROM ASTM F1554 GR 55 S1 HOT ROLL ROUNDS

HOT DIP GALVANIZED PER ASTM A153

ZINC PLATING IS PER ASTM F1941 TYPE V, CLASS SC., 0002 MIN THICKNESS

304SS PER ASTM A193 B8 CLASS 1 GENERALLY WHEN MATERIAL AVAILABLE

316SS PER ASTM A193 B8M CLASS 1 GENERALLY WHEN MATERIAL AVAILABLE

FASTENERS PLUS

FIND IT FAST. GET IT FAST.

STANDARD FIG. 137 LONG TANGENT ROUND UBOLTS

STANDARD FIGURE 137 UBOLTS ARE INTENDED FOR USE WITH SCHEDULE 40 PIPING SYSTEMS

THE INFORMATION ON THIS DRAWING IS INTENDED FOR REFERENCE ONLY

TOLERANCES: (FRACTIONAL = NO LESS THAN +/- 1/8") ANGULAR: (+/- 5°)