

Exterior Nails

Siding, Trim, Shake and Shingle Nail


Features:

- 7/32"-diameter flat head provides ample bearing surface to firmly secure shakes and shingles of all types
- Checker pattern on head blends with wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring-shank increases withdrawal resistance to provide a secure attachment
- Slender shanks minimize splitting
- Diamond point for easier driving
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
3d	1 1/4	14	0.083	7/32	0.219	470	T3SN71	—	T3SN7B
4d	1 1/2	14	0.083	7/32	0.219	394	T4SN71	T4SN75	T4SN7B
5d	1 3/4	14	0.083	7/32	0.219	337	T5SN71	T5SN75	T5SN7B
6d	2	13	0.092	7/32	0.219	237	T6SN71	T6SN75	T6SN7B
7d	2 1/4	13	0.092	7/32	0.219	216	—	T7SN75	T7SN7B
8d	2 1/2	13	0.092	7/32	0.219	196	T8SN71	T8SN75	T8SN7B




Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
3d	1 1/4	14	0.083	7/32	0.219	470	S3SN71	S3SN75	S3SN7B
4d	1 1/2	14	0.083	7/32	0.219	394	S4SN71	S4SN75	S4SN7B
5d	1 3/4	14	0.083	7/32	0.219	337	S5SN71	S5SN75	S5SN7B
6d	2	13	0.092	7/32	0.219	237	S6SN71	S6SN75	S6SN7B
7d	2 1/4	13	0.092	7/32	0.219	216	S7SN71	S7SN75	S7SN7B
8d	2 1/2	13	0.092	7/32	0.219	196	S8SN71	S8SN75	S8SN7B

Siding, Trim, Shake and Shingle Nail

Features:

- Designed expressly for application of various lap and panel siding materials made of fiber-cement composites
- Checker pattern on head blends with faux wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring shank increases withdrawal resistance to provide a secure attachment
- 1 1/4" length has an 1 1/32" head for blind-nailing lap siding
- Diamond point for easier driving
- Recommended for seaside applications and superior corrosion resistance



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
4d	1 1/2	11	0.120	3/8	0.375	179	T4PCS1	T4PCS5	T4PCSB
6d	2	11	0.120	3/8	0.375	144	T6PCS1	T6PCS5	T6PCSB
8d	2 1/2	11	0.120	3/8	0.375	115	T8PCS1*	T8PCS5*	T8PCSB*

*Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.