



# INTERNATIONAL FASTENERS, INC.

## SPEC DATA SUBMITTAL SHEET



### Daggerz™ Drywall Screws • Square Trim • Phosphate

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Head	Thread	Point
6 x 1	18	10,000	<b>TRSQSB06100</b>	#1	Trim	Twin Lead	Pierce
6 x 1-5/8	18	5,000	<b>TRSQSB06158</b>	#1	Trim	Twin Lead	Pierce
6 x 2-1/4	18	3,000	<b>TRSQSB06214</b>	#1	Trim	Twin Lead	Pierce
8 x 3	18	2,000	<b>TRSQSB08300</b>	#2	Trim	Twin Lead	Pierce

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Phosphate Finish provides 48 hour salt spray corrosion resistance
<i>application:</i>	finishing screw, trim through drywall to 25-20 gauge metal studs
<i>installation:</i>	Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.

#### Meets or exceeds the following specifications:

ASME B 18.6.1	Standard Specification for Wood Screws
ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
ASTM C1002	Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs

#### Ultimate Value Chart

	DIAMETER	25 Gauge	22 Gauge	20 Gauge	2 x 4 Red Wood	3/4" particle board	2 x 4 Fir	Min Torsional Strength (Lb)
Tension (Pull) Lbs 1 pc	#6	165	245	349	204	263	396	30 lbs
	#8	149	196	367	206	266	398	39 lbs
Shear (Metal to Metal)	#6	410	601	620	-	-	-	30 lbs
	#8	337	591	829	-	-	-	39 lbs

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

TRSQSB.21