Roofing Nails



15° Wire Coil, Full Round Head, Ring-Shank Roofing Nail


Features:

- Ideal for asphalt and synthetic slate roofing
- Large flat head, diamond point for easier driving
- Annular ring shank increases withdrawal resistance to provide a secure attachment to OSB or plywood roof decks
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance

Compatible Tools

If you don't see your particular model in the table below, see **strongtie.com/toolmatrix** or call Simpson Strong-Tie for assistance with fastener selection (800) 999-5099.

Brand	Model		
Bosch®	RN175		
Bostitch®	RN46		
DeWalt®	D51321		
Grip-Rite®	GRTCR175		
Hitachi®	NV45AB2, NV45AE		
Makita [®]	AN453		
Max [®]	CN445R, CN450R		
Paslode®	R175-C, CR175C		
Porter Cable®	RN175A		
Ridgid [®]	R175RND		
Senco®	RoofPro 455XP		



Type 316 Stainless Steel

Penny Size	Length (in.)	Shank Diameter (in.)	Head Diameter (in.)	Carton Quantity	Model No.
2d	1	0.120	3/8	3,600	T11A100RNJ
3d	11⁄4	0.120	3/8	3,600	T11A125RNJ
4d	1½	0.120	3/8	3,600	T11A150RNJ
5d	13/4	0.120	3/8	3,600	T11A175RNJ

Type 304 Stainless Steel

C-F-2023 @ 2023 SIMPSON STRONG-TIE COMPANY INC.

Type do i Stail illodo Steol								
Penny Size	Length (in.)	Shank Diameter (in.)	Head Diameter (in.)	Carton Quantity	Model No.			
2d	1	0.120	3/8	7,200	S11A100RNB			
3d	11/4	0.120	3/8	7,200	S11A125RNB			
3d	11/4	0.120	3/8	720	S11A125RNBP			
3d	11/4	0.120	3/8	2,400	S11A125RNJ			
4d	1½	0.120	3/8	7,200	S11A150RNB			
4d	1½	0.120	3/8	600	S11A150RNBP			
4d	1½	0.120	3/8	2,400	S11A150RNJ			
5d	13/4	0.120	3/8	7,200	S11A175RNB			
5d	13/4	0.120	3/8	480	S11A175RNBP			
5d	13/4	0.120	3/8	2,400	S11A175RNJ			

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.