

Siding/Fencing/Trim Nails

15° Inserted Plastic Coil, Full Round Head, Ring-Shank Nail

Features:

- Checker pattern on head blends with wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring shank increases withdrawal resistance to provide a secure attachment
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance

Compatible Pneumatic Tools

If you don't see your particular model in the table below, see strongtie.com/toolmatrix or call Simpson Strong-Tie for assistance with fastener selection (800) 999-5099.

| | |
|-------------------|----------------------------------|
| Bostitch® | N64C, N66C, N75C |
| Grip-Rite® | GRTCS250 |
| Hitachi® | NV65AH, NV75AG |
| Max® | CN550S (up to 2"), CN565S, CN565 |
| Senco® | SCN49 |



Type 316 Stainless Steel

| Penny Size | Length (in.) | Shank Diameter (in.) | Head Diameter (in.) | Carton Quantity | Model No. |
|------------|--------------|----------------------|---------------------|-----------------|-------------|
| 4d | 1½ | 0.092 | 0.221 | 3,200 | T13A150IPC |
| 5d | 1¾ | 0.092 | 0.221 | 3,200 | T13A175IPC |
| 5d | 1¾ | 0.092 | 0.221 | 600 | T13A175IPBP |
| 6d | 2 | 0.092 | 0.221 | 3,200 | T13A200IPC |
| 6d | 2 | 0.092 | 0.221 | 600 | T13A200IPBP |
| 7d | 2¼ | 0.092 | 0.221 | 2,400 | T13A225IPC |
| 7d | 2¼ | 0.092 | 0.221 | 600 | T13A225IPBP |
| 8d | 2½ | 0.092 | 0.221 | 2,400 | T13A250IPC |
| 8d | 2½ | 0.092 | 0.221 | 600 | T13A250IPBP |

Type 304 Stainless Steel

| Penny Size | Length (in.) | Shank Diameter (in.) | Head Diameter (in.) | Carton Quantity | Model No. |
|------------|--------------|----------------------|---------------------|-----------------|-------------|
| 4d | 1½ | 0.092 | 0.221 | 3,200 | S13A150IPC |
| 5d | 1¾ | 0.092 | 0.221 | 3,200 | S13A175IPC |
| 6d | 2 | 0.092 | 0.221 | 3,200 | S13A200IPC |
| 7d | 2¼ | 0.092 | 0.221 | 2,400 | S13A225IPC |
| 7d | 2¼ | 0.092 | 0.221 | 600 | S13A225IPBP |
| 8d | 2½ | 0.092 | 0.221 | 2,400 | S13A250IPC |

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.