Adhesive Accessories

Accession

ADT813S Manual Dispensing Tool for 12.5 oz. Cartridges

The ADT813S features a steel carriage for ultimate durability. The ADT813S also features double-gripping plates that help extend tool life.

ADT30S

Manual Dispensing Tool for 30 oz. Adhesive Cartridges

The ADT30S features a steel carriage for ultimate durability and is engineered for continuous, high-volume use, as well as double-gripping plates that help extend tool life. The tool can be easily converted from 30 oz. 10:1 cartridges to 32 oz. 2:1 cartridges.

ADTA30CKT

Battery-Powered Dispensing Tool for 30 oz. Cartridges

The ADTA30C offers power dispensing of 30 oz., 10:1 ratio, dual-cartridge adhesives without the need for a hose or compressor. The tool features dosage and rate control for maximum efficiency on the job. The 18V lithium-ion battery is 50% lighter than NiCad and offers 40% longer run time. Recharging takes only 30 minutes. The ADTA30CKT comes with the dispensing tool, two 18V Lithium-ion battery packs and a charger.

ADTA30P

Pneumatic Dispensing Tool for 30 oz. Cartridges

The ADTA30P tool features an optional suitcase handle adapter for flexible tool configuration and dispensing convenience. The suitcase option enables easier and time-saving ground-level doweling. The heavy-duty tool comes with a custom, blow-molded plastic carrying case. The tool can be easily converted from 30 oz. 10:1 cartridges to 32 oz. 2:1 cartridges.

| Description | Model No. |
|---|-----------|
| Manual tool for 12.5 oz. cartridges | ADT813S |
| Manual tool for 30 oz. cartridges | ADT30S |
| Battery-powered tool for 30 oz. cartridges | ADTA30CKT |
| Pneumatic tool for 30 oz. cartridges ^{1,2} | ADTA30P |

1. Air supply attachment is 1/4-18 NPT (male) thread.

2. Recommended operating air pressure is between 80 and 120 psi .

Maintenance tips, troubleshooting and repair parts schematics available at strongtie.com.







ADTA30CKT



SIMPSO

Strong-Tie

Adhesive Nozzle Accessories

EMN22i

An 18-element mixing nozzle with integrated nut for use with 22 oz. and 56 oz. epoxy adhesive cartridges.

| S |
|----------|
| 5 |
| 0 |
| ē |
| 5 |
| 9 |
| <u> </u> |
| |
| |
| 4 |
| Ð |
| > |
| 10 |
| S |
| (1) |
| - |
| <u> </u> |
| 0 |
| - |
| |

| Model No. | Option | Package Quantity | Carton Quantity |
|--------------|--|---------------------|--------------------|
| EMN22I | 18-element nozzle for 22 oz. and 56 oz.epoxy adhesive. Includes integrated threaded nut for attachment to cartridges. | 1 | 12 |
| EMN22I-RP10 | 18-element nozzle for 22 oz. and 56 oz.epoxy adhesive. Includes integrated threaded nut for attachment to cartridges. | 10 | 3 |
| EMN22I-RP5 | 18-element nozzle for 22 oz. and 56 oz.epoxy adhesive. Includes integrated threaded nut for attachment to cartridges. | 5 | 6 |
| EMN22IB | 18-element nozzle for 22 oz. and 56 oz.epoxy adhesive. Includes integrated threaded nut for attachment to cartridges. | 500 | 500 |

EMN50

A high-volume nozzle for 22 oz. and 56 oz. epoxy cartridges.

| Model No. | Option | Package Quantity |
|--------------|--|---------------------|
| EMN50 | Hi-volume nozzle for 22 oz. and 56 oz. cartridges (separate retaining nut not required), 17" long, major diameter %" | 10 |

AMN19Q

A 19-element high-strength static mixing nozzle for use with all acrylic adhesive products.

AMN19Q

| Model | Option | Package | Carton |
|------------|---|-----------------------|----------|
| No. | | Quantity | Quantity |
| AMN19Q-RP5 | Five mixing nozzles for AT-XP® product. | 5 nozzles per pack | 10 |



EMN22i