

# Exterior Nails


## Roofing Nail — Annular Ring Shank

### Features:

- Large, flat head provides extra bearing surface to firmly secure roofing material
- Annular ring shank increases withdrawal resistance to provide a secure attachment to wood members and plywood roof decks
- Longer lengths ideal for installing curved Spanish roof tiles and thicker slate
- Aluminum nails also available with a screw shank; call Simpson Strong-Tie for details (800) 999-5099

### Installation Tips:


- For slate roofs, determine the correct nail length by doubling the slate thickness and adding one inch



### Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
—	¾	10	0.131	¾	0.375	281	T7510ARN1	T7510ARN5	T7510ARNB
2d	1	10	0.131	¾	0.375	212	T210ARN1	T210ARN5	T210ARNB
3d	1¼	10	0.131	¾	0.375	166	T310ARN1	T310ARN5	T310ARNB
3d	1¼	11	0.120	1½	0.344	199	T311ARN1	—	T311ARNB
4d	1½	10	0.131	¾	0.375	139	T410ARN1	T410ARN5	T410ARNB
4d	1½	11	0.120	1½	0.344	170	T411ARN1	T411ARN5	T411ARNB
5d	1¾	10	0.131	¾	0.375	126	T510ARN1	T510ARN5	T510ARNB
6d	2	10	0.131	¾	0.375	105	T610ARN1	T610ARN5	T610ARNB
8d	2½	10	0.131	¾	0.375	91	T810ARN1*	T810ARN5*	T810ARNB*
10d	3	10	0.131	¾	0.375	78	T1010ARN1*	T1010ARN5*	T1010ARNB*

\*Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.



### Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
—	¾	10	0.131	¾	0.375	281	S7510ARN1	S7510ARN5	S7510ARNB
2d	1	10	0.131	¾	0.375	212	S210ARN1	S210ARN5	S210ARNB
3d	1¼	10	0.131	¾	0.375	166	S310ARN1	S310ARN5	S310ARNB
3d	1¼	11	0.120	¾	0.375	199	—	S311ARN5	S311ARNB
4d	1½	10	0.131	¾	0.375	139	S410ARN1	S410ARN5	S410ARNB
4d	1½	11	0.120	¾	0.375	170	S411ARN1	S411ARN5	S411ARNB
5d	1¾	10	0.131	¾	0.375	126	S510ARN1	S510ARN5	S510ARNB
5d	1¾	11	0.120	¾	0.375	149	—	S511ARN5	S511ARNB
6d	2	10	0.131	¾	0.375	105	S610ARN1	S610ARN5	S610ARNB
6d	2	11	0.120	¾	0.375	136	S611ARN1	—	S611ARNB
8d	2½	10	0.131	¾	0.375	91	S810ARN1*	S810ARN5*	S810ARNB*
10d	3	10	0.131	¾	0.375	78	S1010ARN1*	S1010ARN5*	S1010ARNB*

\*Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.