



Specifications Cordstrap Strapping Solution:

CC Strap 86 UF & Cordstrap Buckle CB8

Performance Specifications			
Performance System (Strapping & Buckle)	1500 daN / 3306 lbf		
System Breaking Strength (SBS) ¹			
Performance Strapping	925 daN / 2039 lbf		
Linear Breaking Strength ¹			
Elongation at Break			
	12 %		
Certification	DNV witnessed		

Strapping Specifications			
Width ²	25 mm / 1"		
Length ²	440 m / 1443 ft		
Core diameter	200 mm / 8"		
Color	white		
Printing	no, printing on request		
Packaging	Quantity	Item number	
Coil	440 m / 1443 ft	7214000	
Cardboard Box	2 coils		
Pallet	60 coils		
Pallet box	n/a		
Material	Recycling symbol/code	Recycled content	Recyclable
High tenacity polyester filament yarn and homopolymer polypropylene	C/PES/PP	0%	No



Represented in over 50 countries
World market leader
ISO 9001:2008 certified
Manufacturer & supplier since 1965
Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance



Buckle Specifications			
Width ²	25 mm / 1"		
Packaging Cardboard Box Pallet	Quantity 250 pieces per box 80 boxes per pallet	Item number 7360500	
Material Galvanized steel wire	Recycling symbol/code FE/40	Recycled content 70%	Recyclable Yes

Packaging material			
Packaging type	Recycling symbol/code	Recycled content	Recyclable
Cardboard Box	LDPE/04	0%	Yes
Pallet box	PAP/20	80%	Yes
Pallet	PAP/20	80%	Yes

Recommended tensioners
CT 40/2; CTT 40; CBT 35 MK2; CT 35 PN

¹Tolerance of +/- 10%

²Tolerance of +/- 2%

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°F and 104°F.
All information provided is based on accuracy at the time of creation.



Represented in over 50 countries

World market leader

ISO 9001:2008 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance

revision date: 24th of October 24