



Collated Exterior Screws


CB3BLG Fiber-Cement Board Screw

Common Applications:
Dense fiber-cement board to wood

Features:

- 0.375" ribbed wafer head with nibs for easy countersinking
- #3 undersized square drive (driver bit in each box; replacement bit model BIT3SU)
- Coarse threads
- Type-17 point
- C-3 mechanically galvanized coating
- Straight collation

Codes/Standards: ANSI A108 compliant



C-3 Mechanically Galvanized Coating

Length (in.)	Shank Size	Threads Per Inch	Contractor Pack		PROLDHG2
			Fasteners Per Pack	Model No.	
1 1/4	#10	10	1,500	CB3BLG114S	✓
1 5/8	#10	10	1,500	CB3BLG158S	✓


CB3BLGHL Cement Board Screw

Common Applications:
Cement board to wood (for coarse, porous and softer materials)

Features:

- 0.375" ribbed wafer head with nibs for easy countersinking
- #3 undersized square drive (driver bit in each box; replacement bit model BIT3SU)
- Alternating high-low threads
- Sharp point
- C-3 mechanically galvanized coating
- Straight collation

Codes/Standards: ANSI A108 compliant



C-3 Mechanically Galvanized Coating

Length (in.)	Shank Size	Threads Per Inch	Contractor Pack		PROLDHG2
			Fasteners Per Pack	Model No.	
1 1/4	#9	15 high-low	1,500	CB3BLGHL114S	✓
1 5/8	#9	15 high-low	1,500	CB3BLGHL158S	✓