


Exterior Nails

Common Nail — Annular Ring Shank

Features:

- Annular ring shank increases withdrawal resistance to provide a secure attachment
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance
- Stainless-steel nails are recommended for construction of permanent wood foundations by the *ANSI/AF&PA Permanent Wood Foundations Design Specifications*



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	15	0.072	3/16	0.188	807	T2ACN1	—	T2ACNB
3d	1¼	14	0.083	7/32	0.219	473	T3ACN1	T3ACN5	T3ACNB
4d	1½	12	0.113	¼	0.250	228	T4ACN1	T4ACN5	T4ACNB
4d	1½	9	0.148	5/16	0.313	130	T4HACN1	T4HACN5	T4HACNB
5d	1¾	12	0.113	¼	0.250	193	T5ACN1	—	T5ACNB
6d	2	11	0.120	17/64	0.266	144	T6ACN1	T6ACN5	T6ACNB
7d	2¼	11	0.120	17/64	0.266	133	—	—	T7ACNB
8d	2½	10	0.131	9/32	0.281	94	T8ACN1**	T8ACN5**	T8ACNB**
10d	3	9	0.148	5/16	0.313	67	T10ACN1*	T10ACN5*	T10ACNB*
12d	3¼	9	0.148	5/16	0.313	60	T12ACN1*	T12ACN5*	T12ACNB*
16d	3½	8	0.162	11/32	0.344	44	T16ACN1	T16ACN5	T16ACNB
20d	4	6	0.203	7/16	0.438	25	T20ACN1	T20ACN5	T20ACNB
30d	4½	6	0.203	7/16	0.438	22	—	—	T30ACNB
40d	5	6	0.203	7/16	0.438	19	T40ACN1	T40ACN5	T40ACNB
60d	6	4	0.238	15/32	0.469	12	—	—	T60ACNB*

*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

**Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.



Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	15	0.072	3/16	0.188	807	S2ACN1	S2ACN5	S2ACNB
2d	1	14	0.083	7/32	0.219	530	S2HACN1	—	S2HACNB
3d	1¼	14	0.083	7/32	0.219	473	S3ACN1	S3ACN5	S3ACNB
4d	1½	12	0.113	¼	0.250	228	S4ACN1	S4ACN5	S4ACNB
5d	1¾	12	0.113	¼	0.250	193	S5ACN1	S5ACN5	S5ACNB
6d	2	11	0.120	17/64	0.266	144	S6ACN1	S6ACN5	S6ACNB
7d	2¼	11	0.120	17/64	0.266	133	S7ACN1	S7ACN5	—
8d	2½	10	0.131	9/32	0.281	94	S8ACN1**	S8ACN5**	S8ACNB**
10d	3	9	0.148	5/16	0.313	67	S10ACN1*	S10ACN5*	S10ACNB*
12d	3¼	9	0.148	5/16	0.313	60	S12ACN1*	S12ACN5*	S12ACNB*
16d	3½	8	0.162	11/32	0.344	44	S16ACN1	S16ACN5	S16ACNB
20d	4	6	0.203	7/16	0.438	25	S20ACN1	S20ACN5	S20ACNB
30d	4½	6	0.203	7/16	0.438	22	S30ACN1	S30ACN5	S30ACNB
40d	5	6	0.203	7/16	0.438	19	S40ACN1	S40ACN5	S40ACNB
60d	6	4	0.238	15/32	0.469	12	—	—	S60ACNB*

*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

**Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.