


**INTERNATIONAL FASTENERS, INC.** 



## SPEC DATA SUBMITTAL SHEET

Dagger-Tite <sup>1</sup>	™ Post	Frame Scre	ws · Hex Washe	er Head I	Hi Low Ty	/pe 17 w	ith Bonded	Washer • Dag	gger-Gua	ard Coating <sup>™</sup>	
Size	TPI	Ctn Qty	Daggerz ™ Pa	Daggerz ™ Part Number		Drive	Head	Head T		Point	
10 x 1	14 2,500		DAGCT1	DAGCT1010T17		1/4"	Hex Wash	er Doubl	e Threac	I Type 17	
10 x 1-1/2	) x 1-1/2 14 2,500		DAGCT10	DAGCT10112T17		1/4"	Hex Wash	er Doubl	e Threac	I Type 17	
10 x 2	10 x 2 14 2,000		DAGCT10	DAGCT1020T17		1/4"	Hex Wash	er Doubl	e Threac	Type 17	
10 x 2-1/2	2-1/2 14 1,500		DAGCT10	DAGCT10212T17		1/4"	Hex Wash	ər Doubl	e Threac	I Type 17	
10 x 3	14	1,000	DAGCT10	)30T17		1/4"	Hex Wash	er Doubl	e Threac	I Type 17	
material: C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425											
finish		Dagger-Guard Coating <sup>™</sup> is a three layer, multi step dip/spin bake process which provides 1000 hour salt spray corrosion resistance									
application	ion: metal to wood applications										
installation	<i>installation:</i> Screw gun with depth sensitive nosepiece with installation speed not to exceed 2500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener is fully seated when the head's bearing surface is flush with the material being attached.										
Meets or exc	ceeds t	he following s	pecifications:								
ASTM A510			Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)								
ASTM B117		Practice	Practice for Operating Salt Spray (Fog) Apparatus								
ASTM C100	2		Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs								
ASTM F1941		Specific	Specification for Electrodeposited Coatings on Threaded Fasteners								
Ultimate Val	ue Cha	rt									
		DIAMETE	ER Nom Screw Dia	25 Gauge	22 Gauge	20 Gauge	2 x 4 Red Wood	3/4" particle board	2 x 4 Fir	Min Torsiona Strength (Lb	
Tension (Pull) Lbs 1 pc		oc 10-14	0.190	173	-	363	-	-	438	56 lbs	
Shear (Metal to Metal)		al) 10-14	0.190	397	-	834	-	-	-	56 lbs	

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes. All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

DAGCT10.21