

Collated Interior Screws


WSHL Subfloor Screw

Common Applications:

- Subfloor to wood

Features:

- Ribbed flat head with nibs for easy countersinking
- #2 square drive (driver bit in each box; replacement bit model BIT2S; see p. 209 for more information)
- High-low threads
- Sharp point
- Curved collation
- 1:1 replacement for 8d common nails when used with floor sheathing 1⁵/₃₂" – 2³/₃₂" thick



Gray Phosphate Coating

Size	Length (in.)	Carton Quantity	Model No.	PRO 200SG2	PRO 250G2
#7	1 3/4	2,000	WSHL134S7	✓	✓

DWC Drywall Screw

Common Applications:

- Drywall to wood

Features:


- Bugle head
- #2 Phillips (driver bit in each box; replacement bit model BIT2P; see p. 209 for more information)
- Coarse threads
- Sharp point
- Curved collation

Codes/Standards: ASTM C1002 Type W



Gray Phosphate Coating

Size	Length (in.)	Contractor Pack		PRO200G2	PRO250DWG2
		Fasteners per Pack	Model No.		
#6	1	2,500	DWC1PS	✓	
#6	1 1/4	2,500	DWC114PS	✓	
#6	1 5/8	2,500	DWC158PS	✓	
#6	2	2,000	DWC2PS	✓	✓
#6	2 1/2	1,500	DWC212PS		✓



Mechanically Galvanized — N2000®

Size	Length (in.)	Contractor Pack		PRO200G2
		Fasteners per Pack	Model No.	
#6	1 5/8	2,500	DWCG158S	✓