




INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Daggerz™ Pro-Seal Washers • EPDM Bonded

Size	I.D. +/- 0.25	O.D. +/- 0.2	EPDM ID	Tm +/- 0.1	Tr +/- 0.2	Material
8-10-12 x 3/4	6.1	19	3.30-3.90	0.8	2	Aluminum
10-12-14 x 1-1/2	7	38	3.95-4.55	1	1.7	Aluminum
8-10 x 1/2	5.4	12.7	3.20-3.70	0.8	2	Galvanized
12 x 9/16	6.1	14	4.25-4.75	0.8	2	Galvanized
14 x 5/8	7.1	16	5.10-5.60	0.8	2	Galvanized
8-10 x 1/2	5.4	12.7	3.20-3.70	0.8	2	Stainless Steel
12 x 9/16	6.1	14	4.25-4.75	0.8	2	Stainless Steel
14 x 5/8	7.1	16	5.10-5.60	0.8	2	Stainless Steel

Note that measurements are in millimeters.

information and specifications:

Aluminum	provides good performance when moderate strength and deflection requirements exist and also minimizes concerns of galvanic corrosion in certain installations
Galvanized	Steel backing material provides good strength characteristics and corrosion resistance
18-8 Stainless Steel	offers optimum corrosion resistance
EPDM	(ETHYLENE PROPYLENE DIENE MONOMER) is an excellent ozone and weather resistant elastomer possessing superior aging characteristics. It has effective heat resistance up to 350 degrees Fahrenheit
Properties	in accordance with ASTM-D412, D624, D792 and D2240 specifications
Heat Resistance	in accordance with ASTM-D573
Ozone Resistance	in accordance with ASTM-D573

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc.
 Appropriate safety factors should be applied to these values for specific purposes.
 All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

NEO.21