

Exterior Screws

Deck-Drive™ DSV WOOD Screw

Preservative-Treated Decking, Exterior Wood and Engineered Wood Applications


The Deck-Drive DSV Wood screw is a powerful fastening solution for preservative-treated decking applications. With its Underhead ribs and fast-start tip, the DSV is ideally suited to be driven and countersunk into today's wood deck boards. The shank is designed to withstand the swelling and shrinkage that is common with fast-growth lumber. Available in hand-drive and in collated strips for use in our Quik Drive® auto-feed screw driving system, DSV screws are also offered in a variety of sizes to fasten fascia and trim.

Features:

- Low-torque threads allow up to 35% more screws to be driven on a battery charge
- Ribbed-head design countersinks easily and provides a clean, finished appearance
- High-low tip provides fast starts
- Optimized threads for dimensional lumber
- Quik Guard® coating provides corrosion resistance for exterior and certain preservative-treated wood applications as described by ICC-ES AC257, exposure conditions 1 and 3
- Color blends with wood decking
- T-25 6-lobe driver bit included (replacement driver bit — BIT25T-2)


This screw is also available collated for the Quik Drive system. See p. 190 for details.

US Patent 6,074,149



Quik Guard® Coating – Tan

| Size | Length (in.) | Head Dia. (in.) | Approx. Count Per Pound | 1 lb. Model No. | 5 lb. Model No. | 350 ct. Model No. | Mini-Bulk | |
|------|--------------|-----------------|-------------------------|-----------------|-----------------|-------------------|-----------|-------|
| | | | | | | | Model No. | Count |
| #8 | 1 1/4 | 0.33 | 194 | DSVT114R1LB | DSVT114R5LB | DSVT114R350 | DSVT114MB | 1,750 |
| #8 | 1 5/8 | 0.33 | 159 | DSVT158R1LB | DSVT158R5LB | DSVT158R350 | DSVT158MB | 1,750 |
| #10 | 2 | 0.33 | 113 | DSVT2R1LB | DSVT2R5LB | DSVT2R350 | DSVT2MB | 1,750 |
| #10 | 2 1/2 | 0.33 | 91 | DSVT212R1LB | DSVT212R5LB | DSVT212R350 | DSVT212MB | 1,750 |
| #10 | 3 | 0.33 | 76 | DSVT3R1LB | DSVT3R5LB | DSVT3R350 | DSVT3MB | 1,750 |
| #10 | 3 1/2 | 0.33 | 66 | DSVT312R1LB | DSVT312R5LB | DSVT312R350 | DSVT312MB | 1,000 |
| #10 | 4 | 0.33 | 59 | DSVT4R1LB | DSVT4R5LB | DSVT4R350 | DSVT4MB | 1,000 |



Quik Guard Coating – Red

| Size | Length (in.) | Head Dia. (in.) | Approx. Count Per Pound | 1 lb. Model No. | 5 lb. Model No. | 350 ct. Model No. | Mini-Bulk | |
|------|--------------|-----------------|-------------------------|-----------------|-----------------|-------------------|-----------|-------|
| | | | | | | | Model No. | Count |
| #8 | 1 1/4 | 0.33 | 194 | DSVR114R1LB | DSVR114R5LB | DSVR114R350 | DSVR114MB | 1,750 |
| #8 | 1 5/8 | 0.33 | 159 | DSVR158R1LB | DSVR158R5LB | DSVR158R350 | DSVR158MB | 1,750 |
| #10 | 2 | 0.33 | 113 | DSVR2R1LB | DSVR2R5LB | DSVR2R350 | DSVR2MB | 1,750 |
| #10 | 2 1/2 | 0.33 | 91 | DSVR212R1LB | DSVR212R5LB | DSVR212R350 | DSVR212MB | 1,750 |
| #10 | 3 | 0.33 | 76 | DSVR3R1LB | DSVR3R5LB | DSVR3R350 | DSVR3MB | 1,750 |
| #10 | 3 1/2 | 0.33 | 66 | DSVR312R1LB | DSVR312R5LB | DSVR312R350 | DSVR312MB | 1,000 |
| #10 | 4 | 0.33 | 59 | DSVR4R1LB | DSVR4R5LB | DSVR4R350 | DSVR4MB | 1,000 |