



INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Daggerz™ Acoustical Eye Lag Screws • Sharp Point • Zinc

| Size | TPI | Ctn Qty | Daggerz™ Part Number | Hole Diameter | Thread Length | Point |
|--------|-----|---------|----------------------|---------------|---------------|-------|
| 14 x 3 | 11 | 1,000 | ELSZ1430 | 3/16" | 1-5/8" | Sharp |

| | |
|---------------------|---|
| <i>material:</i> | C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425 |
| <i>finish:</i> | Zinc Finish provides 24 hour minimum salt spray corrosion resistance |
| <i>application:</i> | used to attach wire for interior suspended ceiling systems; drywall or insulation to wood |

Meets or exceeds the following specifications:

| | |
|------------|--|
| ASTM A510 | Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018) |
| ASTM B117 | Practice for Operating Salt Spray (Fog) Apparatus |
| ASTM C1002 | Standard Specification for Steel Self-Piercing Tapping Screws for Application of Gypsum Panel Products or Metal Plaster Bases to Wood Studs or Steel Studs |

Ultimate Value Chart

| DIAMETER | 1/2" Plywood | 5/8" Plywood | 3/4" Plywood | 2 x 4 |
|----------|--------------|--------------|--------------|-------|
| #14 | 434 | 475 | 626 | 1030 |

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc.
 Appropriate safety factors should be applied to these values for specific purposes.
 All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

ELSZ.21