


## Exterior Nails

### Box Nail — Annular Ring Shank

#### Features:


- Checker pattern on head blends with wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring shank increases withdrawal resistance to provide a secure attachment
- Stainless-steel nails are recommended for construction of permanent wood foundations by the *ANSI/AF&PA Permanent Wood Foundations Design Specifications*
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance



#### Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
3d	1¼	14	0.083	7/32	0.219	473	—	—	T3ABNB
4d	1½	14	0.083	7/32	0.219	413	T4ABN1	T4ABN5	—
5d	1¾	13	0.092	19/64	0.203	260	T5ABN1	T5ABN5	T5ABNB
6d	2	12	0.113	17/64	0.266	175	T6ABN1	T6ABN5	T6ABNB
8d	2½	12	0.113	17/64	0.266	138	T8ABN1	T8ABN5	T8ABNB
10d	3	11	0.120	17/64	0.266	99	T10ABN1	T10ABN5	T10ABNB
12d	3¼	10	0.131	9/32	0.281	72	T12ABN1	T12ABN5	—
16d	3½	10	0.131	9/32	0.281	67	T16ABN1	T16ABN5	T16ABNB
20d	4	8	0.162	11/32	0.344	40	—	—	T20ABNB*

\*Complies with ASTM F1667 specifications for post-frame ring-shank nails.




#### Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
3d	1¼	14	0.083	7/32	0.219	473	S3ABN1	S3ABN5	S3ABNB
4d	1½	14	0.083	7/32	0.219	413	S4ABN1	S4ABN5	S4ABNB
5d	1¾	13	0.092	19/64	0.203	260	S5ABN1	S5ABN5	S5ABNB
6d	2	12	0.113	17/64	0.266	175	S6ABN1	S6ABN5	S6ABNB
8d	2½	12	0.113	17/64	0.266	138	S8ABN1	S8ABN5	S8ABNB
10d	3	11	0.120	17/64	0.266	99	S10ABN1	S10ABN5	S10ABNB
12d	3¼	10	0.131	9/32	0.281	72	S12ABN1	S12ABN5	S12ABNB
16d	3½	10	0.131	9/32	0.281	67	S16ABN1	S16ABN5	S16ABNB

### Box Nail — Screw-Shank Nail

#### Features:

- Checker pattern head blends with wood grain, reduces glare from sunlight and accepts surface finishes
- Screw shank increases withdrawal resistance to provide a secure attachment
- Stainless steel nails are recommended for construction of permanent wood foundations by the *ANSI/AF&PA Permanent Wood Foundations Design Specifications*
- Type 316 stainless steel



#### Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
6d	2	12	0.113	17/64	0.266	175	T6SBX1	T6SBX5	T6SBXB
8d	2½	12	0.113	17/64	0.266	138	T8SBX1	T8SBX5	T8SBXB
10d	3	11	0.12	17/64	0.266	99	T10SPBX1	T10SPBX5	T10SPBXB

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.