

Metal Screws

Strong-Drive® FPHSD FRAMING-TO-CFS Screw

Cold-Formed Steel Framing

Common Applications:

- Cold-formed steel framing and sheet steel sheathing to cold-formed steel


Features:

- Flat pan head
- Self-drilling
- #3 square drive (driver bit in each box; replacement bit model BIT3S-2-R2)
- This screw is also available collated for the Quik Drive® system; see p. 237 for details

For more information regarding driver bits for Simpson Strong-Tie fasteners, see p. 129.

Codes/Standards: ASTM C1513 compliant; ICC-ES ESR-3006 (including City of LA Supplement), State of Florida FL35320

For Technical Data and Loads, see C-F-2023TECHSUP *Fastening Systems Technical Guide*, pp. 222–223, 227



Clear Zinc Coating

Size	Length (in.)	Max. Grip Length (in.)	Threads per Inch	Head Diameter (in.)	Point Size	Approx. Count per lb.	1 lb. Model No.	Bulk	
								Carton Quantity	Model No.
#10	3/4	0.257	16	0.370	#3	165	FPHSD34B1016	5,000	FPHSD34B1016-5K
#12	3/4	0.233	14	0.370	#3	147	FPHSD34B1214	5,000	FPHSD34B1214-5K

1. Grip length includes side member, steel thickness, air gap (if any) and allowance for three threads protruding through the steel.
2. Has underhead nibs.