


Framing Nails – Plastic Strip

20°–22° Plastic Strip, Full Round Head, Ring-Shank Nail

Features:

- Checker pattern on head blends with the wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring shank increases withdrawal resistance to provide a secure attachment
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance
- 2 3/8" or longer have painted tips



Compatible Pneumatic Tools

If you don't see your particular model in the table below, see strongtie.com/toolmatrix or call Simpson Strong-Tie for assistance with fastener selection (800) 999-5099.

Bosch®	SN350-20F (up to 0.148")	Makita®	AN923
Bostitch®	F21PL	Max®	SN883RH (up to 0.148", 3/4"), SN883RH2 (up to 0.148", 3/4") SN890RH (up to 0.148")
DeWalt®	D51850 (up to 0.148"), D51844 (up to 0.148")	Porter Cable®	FR350MAG, FR350A (up to 0.148")
Grip-Rite®	GRTFR83 (up to 0.131", 3/4"), GRTRH350 (up to 0.148")	Ridgid®	R350RHA
Hitachi®	NR83AS (up to 0.131", 3/4"), NR90AC3, NR90AEPR (up to 0.148"), NR90GR (up to 0.131"), NR90GR2 (up to 0.131")	Senco®	SN902XP (up to 0.148", 3/4"), SN952XP (up to 0.148"), GT90FRH (up to 0.131") FramePro 602 (up to 0.148"), FramePro 702XP (up to 0.148"), FramePro 752XP

Type 316 Stainless Steel

Penny Size	Length (in.)	Shank Diameter (in.)	Head Diameter (in.)	Carton Quantity	Model No.
6d	2	0.113	9/32	5,000	T12A200CNB
6d	2	0.113	9/32	1,000	T12A200CNJ
8d	2 3/8	0.113	9/32	5,000	T12A237CNB
8d	2 3/8	0.113	9/32	1,000	T12A237CNJ
8d	2 1/2	0.120	9/32	4,000	T11A250CNB
8d	2 1/2	0.120	9/32	1,000	T11A250CNJ
10d	3	0.120	9/32	4,000	T11A300CNB
10d	3	0.120	9/32	1,000	T11A300CNJ
10d	3	0.131	9/32	4,000	T10A300CNB
10d	3	0.131	9/32	1,000	T10A300CNJ
12d	3 1/4	0.120	9/32	4,000	T11A325CNB
12d	3 1/4	0.120	9/32	1,000	T11A325CNJ
12d	3 1/4	0.131	9/32	4,000	T10A325CNB
12d	3 1/4	0.131	9/32	1,000	T10A325CNJ
16d	3 1/2	0.131	9/32	4,000	T10A350CNB
16d	3 1/2	0.131	9/32	1,000	T10A350CNJ

Type 304 Stainless Steel

Penny Size	Length (in.)	Shank Diameter (in.)	Head Diameter (in.)	Carton Quantity	Model No.
6d	2	0.113	9/32	5,000	S12A200CNB
6d	2	0.113	9/32	1,000	S12A200CNJ
6d	2	0.120	9/32	5,000	S11A200CNB
6d	2	0.120	9/32	1,000	S11A200CNJ
8d	2 3/8	0.113	9/32	5,000	S12A237CNB
8d	2 3/8	0.113	9/32	1,000	S12A237CNJ
8d	2 1/2	0.120	9/32	4,000	S11A250CNB
8d	2 1/2	0.120	9/32	1,000	S11A250CNJ
8d	2 1/2	0.131	9/32	4,000	S10A250CNB
10d	3	0.120	9/32	4,000	S11A300CNB
10d	3	0.120	9/32	1,000	S11A300CNJ
10d	3	0.131	9/32	4,000	S10A300CNB
10d	3	0.131	9/32	1,000	S10A300CNJ
12d	3 1/4	0.120	9/32	4,000	S11A325CNB
12d	3 1/4	0.120	9/32	1,000	S11A325CNJ
12d	3 1/4	0.131	9/32	4,000	S10A325CNB
12d	3 1/4	0.131	9/32	1,000	S10A325CNJ
16d	3 1/2	0.131	9/32	4,000	S10A350CNB
16d	3 1/2	0.131	9/32	1,000	S10A350CNJ

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.