



D	L	C	A	T	WT. PER C
3/8"-16	8"	1/2"	1"	3"	25
3/8"-16	10"	1/2"	1"	3"	30
3/8"-16	12"	1/2"	1"	3"	35
3/8"-16	14"	1/2"	1"	3"	40
1/2"-13	8"	5/8"	1 1/4"	4"	46
1/2"-13	10"	5/8"	1 1/4"	4"	55
1/2"-13	12"	5/8"	1 1/4"	4"	64
1/2"-13	16"	5/8"	1 1/4"	4"	81
1/2"-13	18"	5/8"	1 1/4"	4"	90
5/8"-11	8"	3/4"	1 1/4"	4"	74
5/8"-11	10"	3/4"	1 1/4"	4"	88
5/8"-11	12"	3/4"	1 1/4"	4"	102
5/8"-11	14"	3/4"	1 1/4"	4"	115
5/8"-11	18"	3/4"	1 1/4"	4"	143
5/8"-11	24"	3/4"	1 1/4"	4"	185
3/4"-10	8"	1 1/8"	1 1/2"	5"	118
3/4"-10	10"	1 1/8"	1 1/2"	5"	139
3/4"-10	12"	1 1/8"	1 1/2"	5"	160
3/4"-10	14"	1 1/8"	1 1/2"	5"	180
3/4"-10	18"	1 1/8"	1 1/2"	5"	220
3/4"-10	24"	1 1/8"	1 1/2"	5"	285
1"-8	10"	2 1/8"	3 1/4"	6"	300
1"-8	12"	2 1/8"	3 1/4"	6"	338
1"-8	18"	2 1/8"	3 1/4"	6"	451
1"-8	24"	2 1/8"	3 1/4"	6"	563

**\*\* NOT ALL SIZES ARE STOCKED AT ALL TIMES \*\***

AVAILABLE IN HOT DIP GALVANIZED

ALSO AVAILABLE IN PLAIN, ZINC CLEAR, 304SS & 316SS UPON SPECIAL ORDER AT CURRENT MARKET PRICE

ITEMS ARE PITCH BODY UNDERSIZED WITH ROLLED THREADS

COMMERCIAL NUT FIT \*\* NOT UNC-2A FIT \*\*

USA DOMESTIC MANUFACTURE

**SOLD BULK NO NUTS UNLESS SPECIFICALLY QUOTED OTHERWISE**

DIAMETERS 1/2"-13 THRU 5/8"-11 GENERALLY MADE FROM COLD DRAWN 1006-1018 COIL STEEL

DIAMETERS 3/4"-10 AND UP GENERALLY MADE FROM ASTM F1554 GR 55 S1 HOT ROLL ROUNDS

HOT DIP GALVANIZED PER ASTM A153

ZINC PLATING IS PER ASTM F1941 TYPE V, CLASS SC., 0002 MIN THICKNESS

304SS PER ASTM A193 B8 CLASS 1 GENERALLY WHEN MATERIAL AVAILABLE

316SS PER ASTM A193 B8M CLASS 1 GENERALLY WHEN MATERIAL AVAILABLE

**FASTENERS PLUS**

FIND IT FAST. GET IT FAST.

**ROUND SHAPE J ANCHORS**

THE INFORMATION ON THIS DRAWING IS INTENDED FOR REFERENCE ONLY  
 TOLERANCES: ( FRACTIONAL = NO LESS THAN +/- 1/8" ) ANGULAR: ( +/- 5° )