




# INTERNATIONAL FASTENERS, INC.

## SPEC DATA SUBMITTAL SHEET



### Daggerz™ Self Drill Screws • Hex Washer Head with Bonded Washer • 410 Stainless Steel

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Drill Point	Max Drill	Drill Speed
14 x 3/4	14	2,500	<b>NEOSDSS14034</b>	3/8"	#3 PT	0.220"	1500 RPM
14 x 1	14	2,500	<b>NEOSDSS1410</b>	3/8"	#3 PT	0.220"	1500 RPM
14 x 1-1/4	14	2,000	<b>NEOSDSS141104</b>	3/8"	#3 PT	0.220"	1500 RPM
14 x 1-1/2	14	1,500	<b>NEOSDSS14112</b>	3/8"	#3 PT	0.220"	1500 RPM
14 x 2	14	1,500	<b>NEOSDSS1420</b>	3/8"	#3 PT	0.220"	1500 RPM
14 x 2-1/2	14	1,000	<b>NEOSDSS14212</b>	3/8"	#3 PT	0.220"	1500 RPM

<i>material:</i>	410 STAINLESS STEEL, CASE HARDNESS: HV500 MINIMUM
<i>application:</i>	metal to metal applications.
<i>installation:</i>	Screw gun with depth sensitive nose piece with installation speed not to exceed 1500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener must penetrate beyond the metal with a minimum of three threads protruding past the back side of the metal.

*Meets or exceeds the following specifications:*

AC118	Acceptance criteria for tapping screw fasteners used in steel-to-steel connections
ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
ASTM C1513 (18)	Standard Specification for Steel Tapping Screws for Cold-Formed Steel Framing Connections
SAE J78	Standard for Dimensional, Mechanical and Performance Requirements

*Ultimate Value Chart*

	DIAMETER	Nom Screw Dia	22 Gauge	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge	3/16"	Min Torsional Strength (Lb)
Tension (Pull) Lbs 1 pc	14-14	0.250	-	300	402	776	1057	1477	3941	156 lbs
Shear (Metal to Metal)	14-14	0.250	-	797	1083	1942	2300	2754	-	156 lbs

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes.  
All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

NEOSDSS14.21.1