

INTERNATIONAL FASTENERS, INC.



SPEC DATA SUBMITTAL SHEET

Size	TPI	Ctn Qty	Daggerz™ Part Number	Drive	Drill Point	Max Drill	Drill Speed						
14 x 7/8	14	2,500	NEOSTHCT1478	5/16"	#1 PT	0.110	1500 RPM						
material:	C1022 LO	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425											
finish:	Dagger-Guard Coating™ is a three layer, multi step dip/spin bake process which provides 1000 hour salt spray corrosion resistance												
application:	metal to m	netal to metal applications.											
	Screw gun with depth sensitive nosepiece with installation speed not to exceed 1500 RPM. Overdriving may result in fastener failure or strikeout of the work surface. The fastener must penetrate beyond the metal with a minimum of three threads protruding past the back side of the metal.												
installation:													
Installation: Meets or exc	minimum o	f three threa	ds protruding past the back side										
	minimum o	f three threa	ds protruding past the back side	e of the meta	ıl.	-							
Meets or exc	minimum o eeds the foll A S	f three thread owing specif acceptance c	ds protruding past the back side <i>fications:</i> riteria for tapping screw fastene for General Requirements for V	e of the meta ers used in s	II. teel-to-steel co	nnections							
<i>Meets or exc</i> AC118	minimum o eeds the foll A S (f three threa owing specif acceptance c Opecification Minimum gra	ds protruding past the back side <i>fications:</i> riteria for tapping screw fastene for General Requirements for V	e of the meta ers used in s Vire Rods an	II. teel-to-steel co	nnections							
<i>Meets or exc</i> AC118 ASTM A510	minimum o eeds the foll A S ((F	f three threa owing specif acceptance c Opecification Minimum gra Practice for C	ds protruding past the back side <i>fications:</i> riteria for tapping screw fastene for General Requirements for V ade 1018)	e of the meta ers used in s Vire Rods an aratus	teel-to-steel co d Coarse Rour	nnections nd Wire, Carbo	n Steel						
<i>Meets or exce</i> AC118 ASTM A510 ASTM B117	minimum o eeds the foll A S S S S S (18) S	f three threa owing specif acceptance c Specification Minimum gra Practice for C Standard Specification	ds protruding past the back side <i>fications:</i> riteria for tapping screw fastene for General Requirements for V ade 1018) Operating Salt Spray (Fog) Appa	e of the meta ers used in s Vire Rods an aratus ews for Cold	II. teel-to-steel co d Coarse Rour -Formed Steel	nnections nd Wire, Carbo	n Steel						
<i>Meets or exc</i> AC118 ASTM A510 ASTM B117 ASTM C1513	minimum o eeds the foll S (18) S (18) S (18) S (18)	f three threa owing specif acceptance c specification Minimum gra Practice for C standard Spe specification	ds protruding past the back side <i>fications:</i> riteria for tapping screw fastene for General Requirements for V ade 1018) Operating Salt Spray (Fog) Appa ecification for Steel Tapping Scre	e of the meta ers used in s Vire Rods an aratus ews for Cold on Threadec	II. teel-to-steel co d Coarse Rour -Formed Steel I Fasteners	nnections nd Wire, Carbo	n Steel						

	DIAMETER	Nom Screw Dia	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge	3/16"	7/32"	Min Torsional Strength (Lb)
Tension (Pull) Lbs 1 pc	14-14	0.250	300	402	776	1057	1477	3941	4645	156 lbs
Shear (Metal to Metal)	14-14	0.250	797	1083	1942	2300	2754	-	-	156 lbs

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc. Appropriate safety factors should be applied to these values for specific purposes.

All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

NEOSTHCT.21.1