Indoor Architectural Products



Ornamental — Joist Hanger

The OHU ornamental joist hangers are heavy-duty, load-rated joist hangers that are attached with ¼" x 3" Strong-Drive® double-barrier coating SDS Heavy-Duty Connector screws (supplied with product).


Material: 12 gauge


Finish: Black powder coat

Options:

No modifications

Codes: See p. 11 for Code Reference Key Chart





Typical OHU Installation

Model No.	Joist Size	Ga.	Dimensions (in.)			No. of 1/4" x 3" SDS		DF/SP Allowable Loads				SPF/HF Allowable Loads				Code
			W	Н	В	Wood Screws		Uplift	Floor	Snow	Roof	Uplift	Floor	Snow	Roof	Ref.
						Face	Joist	(160)	(100)	(115)	(125)	(160)	(100)	(115)	(125)	
0HU46-SDS3	4x6	12	3%16	5	4	6	4	1,930	2,520	2,900	3,150	1,390	1,800	2,070	2,250	
OHU48-SDS3	4x8	12	3%16	6¾	4	8	6	2,765	3,360	3,865	4,200	1,990	2,400	2,760	3,000	
OHU410-SDS3	4x10	12	3%16	8¾	4	12	6	2,765	5,040	5,795	6,300	1,990	3,600	4,140	4,500	
0HU412-SDS3	4x12	12	3%16	10¾	4	12	8	3,565	5,040	5,795	6,300	2,570	3,600	4,140	4,500	
OHU414-SDS3	4x14	12	3%16	12¾	4	14	10	3,565	5,880	6,760	7,350	2,570	4,200	4,830	5,250	
OHU66-SDS3	6x6	12	5½	5	4	6	4	1,930	2,520	2,900	3,150	1,390	1,800	2,070	2,250	-
OHU68-SDS3	6x8	12	5½	7	4	12	6	2,765	5,040	5,795	5,955	1,990	3,600	4,140	4,290	
OHU610-SDS3	6x10	12	5½	9	4	14	6	2,765	5,880	6,760	6,885	1,990	4,200	4,830	4,960	
OHU612-SDS3	6x12	12	5½	11	4	16	8	3,565	6,720	7,730	7,815	2,570	4,800	5,520	5,630	
OHU614-SDS3	6x14	12	5½	13	4	18	10	3,565	7,560	8,695	8,745	2,570	5,400	6,210	6,300	

- 1. Uplift loads have been increased for earthquake or wind loading with no further increase allowed. Reduce where other loads govern.
- 2. Fasteners: SDS screws are Simpson Strong-Tie® Strong-Drive SDS Heavy-Duty Connector screws. See pp. 21–22 for fastener information.

Special Order Parts


Simpson Strong-Tie can make a variety of flat and bent steel shapes, which include gusset plates for heavy timber trusses, custom ornamental shapes and retaining plates.

Material: 3 gauge maximum


Finish: Galvanized, black powder coat, Simpson Strong-Tie gray paint, stainless steel. Contact Simpson Strong-Tie for availability.

To Obtain a Quote:

- Supply a CAD drawing in .dxf format complete with plate dimensions, hole diameter and locations, steel thickness, desired finish (Simpson Strong-Tie gray paint, black powder-coat, HDG or raw steel)
- Total plate shape and size up to maximum dimensions of 48" x 48" (approx. 1/16" tolerance)
- Simpson Strong-Tie does not provide product engineering or load values for special order plates
- Contact Simpson Strong-Tie for pricing information
- Refer to General Notes, note g on p. 17 for additional information



"W" and "H" indicate the envelope size of the steel shape.



Typical Installation (plate shown has black powder coat)