



Collated Exterior Screws

PC Standing-Seam-Roofing Panel Clip Screw

Common Applications:

Standing-seam-roofing panel clips to wood

Features:

- Pancake head
- #2 square drive (driver bit in each box; replacement bit model BIT2SU)
- Type-17 point
- Straight collation

Codes/Standards: ASTM C1513 compliant

Warning: Industry studies show that hardened fasteners can experience performance problems in wet or corrosive environments. Accordingly, use this product in dry, interior and noncorrosive environments only.

Quik Guard® Coating



Length (in.)	Shank Size	Threads Per Inch	Carton Quantity	Model No.	PROPP150G2
1 1/2	#10	12	1,500	PCQ112BS1012	✓

WSC Wood Screw


Common Applications:

Wood to wood

Features:

- Flat head with nibs under the head for easier countersinking
- #2 square drive (replacement bit models BIT2SU)
- Coarse threads
- Curved collation

N2000® Coating



Length (in.)	Shank Size	Point Type	Carton Quantity	Model No.	PR0200SG2	PR0250G2	PR0300SG2
1 3/4	#8	Sharp point	2,000	WSCG134S	✓	✓	✓



Collated Interior Screws

PC Standing-Seam-Roofing Panel Clip Screw

Common Applications:

Standing-seam-roofing panel clips to wood

Features:

- Pancake head
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- Type-17 point
- Straight collation
- Type 410 stainless steel is coated for additional corrosion protection



Type 410 Stainless Steel*

Length (in.)	Shank Size	#2 Drive Type	Threads Per Inch	Carton Quantity	Model No.	PROPP150G2
1	#10	Standard	12	1,500	SSPC1BS1012	✓

* These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.



Clear Zinc Coating

Length (in.)	Shank Size	#2 Drive Type	Threads Per Inch	Carton Quantity	Model No.	PROPP150G2
1	#10	Standard	12	1,500	PC1BS1012	✓