

Exterior Nails


Premium Siding Nail

Common Application:

Siding in severe-exposure environments

Features:

- Type 316 stainless steel for seaside applications and severe-exposure environments
- Passivated to ensure corrosion resistance
- Circle pattern head reduces glare and accepts surface finishes
- Annular ring shank increases pull-out resistance, provides greater holding power
- Blunt diamond point drives true and reduces board splitting



Type 316 Stainless Steel

Penny Size	Length (in.)	Wire Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
2d	1	15	0.072	5/32	0.156	807	T2KR51	T2KR55	T2KR5B
2d	1	14	0.083	7/32	0.219	530	T2KR71	T2KR75	—
3d	1 ¼	14	0.083	5/32	0.156	495	T3KR51	T3KR55	T3KR5B
3d	1 ¼	14	0.083	7/32	0.219	470	T3KR71	T3KR75	T3KR7B
4d	1 ½	14	0.083	5/32	0.156	398	T4KR51	T4KR55	T4KR5B
4d	1 ½	14	0.083	7/32	0.219	394	T4KR71	T4KR75	T4KR7B
5d	1 ¾	14	0.083	5/32	0.156	354	T5KR51	T5KR55	T5KR5B
5d	1 ¾	14	0.083	7/32	0.219	337	T5KR71	T5KR75	T5KR7B
6d	2	14	0.083	5/32	0.156	402	T6KR51	T6KR55	T6KR5B
6d	2	13	0.092	7/32	0.219	261	T6KR71	T6KR75	T6KR7B
7d	2 ¼	13	0.092	5/32	0.156	215	T7KR51	T7KR55	T7KR5B
7d	2 ¼	13	0.092	7/32	0.219	216	T7KR71	T7KR75	T7KR7B
8d	2 ½	13	0.092	5/32	0.156	196	T8KR51	T8KR55	T8KR5B
8d	2 ½	13	0.092	7/32	0.219	196	T8KR71	T8KR75	T8KR7B
10d	3	12	0.113	7/32	0.219	120	T10KR71	T10KR75	T10KR7B
16d	3 ½	11	0.120	¼	0.250	88	T16KR41	T16KR45	T16KR4B


Premium Common Nail

Common Application:

Fastening in severe-exposure environments

Features:

- Type 316 stainless steel for seaside applications and severe-exposure environments
- Passivated to ensure corrosion resistance
- Circle pattern head reduces glare and accepts surface finishes
- Annular ring shank increases pull-out resistance, provides greater holding power
- Blunt diamond point drives true and reduces board splitting



Penny Size	Length (in.)	Wire Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
6d	2	11	0.120	17/64	0.266	144	T6AKR1	T6AKR5	T6AKRB
8d	2 ½	10	0.131	9/32	0.281	94	T8AKR1	T8AKR5	T8AKRB
10d	3	9	0.148	5/16	0.312	67	T10AKR1**	T10AKR5**	T10AKRB**
12d	3 ¼	9	0.148	5/16	0.312	60	T12AKR1*	T12AKR5*	T12AKRB*
16d	3 ½	8	0.162	11/32	0.344	44	T16AKR1*	T16AKR5*	T16AKRB*

*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

**Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.