


Exterior Nails

Decking and General Wood Construction Nail — Annular Ring Shank

Features:

- Annular ring shank increases withdrawal resistance to provide a secure attachment
- Stainless-steel nails are recommended for construction of permanent wood foundations by the *ANSI/AWC Permanent Wood Foundations Design Specifications*
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance




Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	15	0.072	3/16	0.188	807	T2ACN1	—	T2ACNB
3d	1¼	14	0.083	7/32	0.219	473	T3ACN1	T3ACN5	T3ACNB
4d	1½	12	0.113	¼	0.250	228	T4ACN1	T4ACN5	T4ACNB
4d	1½	9	0.148	5/16	0.313	130	T4HACN1	T4HACN5	T4HACNB
6d	2	11	0.120	17/64	0.266	144	T6ACN1	T6ACN5	T6ACNB
8d	2½	10	0.131	9/32	0.281	94	T8ACN1**	T8ACN5**	T8ACNB**
10d	3	9	0.148	5/16	0.313	67	T10ACN1*	T10ACN5*	T10ACNB*
12d	3¼	9	0.148	5/16	0.313	60	T12ACN1*	T12ACN5*	T12ACNB*
16d	3½	8	0.162	11/32	0.344	44	T16ACN1	T16ACN5	T16ACNB
20d	4	6	0.203	7/16	0.438	25	T20ACN1	T20ACN5	T20ACNB
30d	4½	6	0.203	7/16	0.438	22	—	—	T30ACNB
40d	5	6	0.203	7/16	0.438	19	T40ACN1	T40ACN5	T40ACNB
60d	6	4	0.238	15/32	0.469	12	—	—	T60ACNB*

*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

**Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.



Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	15	0.072	3/16	0.188	807	S2ACN1	S2ACN5	S2ACNB
2d	1	14	0.083	7/32	0.219	530	S2HACN1	—	S2HACNB
3d	1¼	14	0.083	7/32	0.219	473	S3ACN1	S3ACN5	S3ACNB
4d	1½	12	0.113	¼	0.250	228	S4ACN1	S4ACN5	S4ACNB
6d	2	11	0.120	17/64	0.266	144	S6ACN1	S6ACN5	S6ACNB
8d	2½	10	0.131	9/32	0.281	94	S8ACN1**	S8ACN5**	S8ACNB**
10d	3	9	0.148	5/16	0.313	67	S10ACN1*	S10ACN5*	S10ACNB*
12d	3¼	9	0.148	5/16	0.313	60	S12ACN1*	S12ACN5*	S12ACNB*
16d	3½	8	0.162	11/32	0.344	44	S16ACN1	S16ACN5	S16ACNB
20d	4	6	0.203	7/16	0.438	25	S20ACN1	S20ACN5	S20ACNB
30d	4½	6	0.203	7/16	0.438	22	S30ACN1	S30ACN5	S30ACNB
40d	5	6	0.203	7/16	0.438	19	S40ACN1	S40ACN5	S40ACNB
60d	6	4	0.238	15/32	0.469	12	—	—	S60ACNB*

*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

**Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.