

Exterior Nails

Roofing Nail — Annular Ring Shank

Features:

- Large, flat head provides extra bearing surface to firmly secure roofing material
- Annular ring shank increases withdrawal resistance to provide a secure attachment to wood members and plywood roof decks
- Longer lengths ideal for installing curved Spanish roof tiles and thicker slate

Installation Tips:

- For slate roofs, determine the correct nail length by doubling the slate thickness and adding one inch



Type 304 Stainless Steel


Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	25 lb. Bucket Model No.
40d	5	8	0.162	½	28	S40ATNB*

*Complies with ASTM F1667 specifications for post-frame ring-shank nails.

Specialty Nail — Fencing Staples

Type 304 Stainless Steel

Length (in.)	Screw Size/ Nail Gauge	Count per lb. (approx.)	Package Size	Model No.
1¼	13	202	1 lb.	S13125FS1
1¼	13	202	5 lb.	S13125FS5
1¼	13	202	25 lb.	S13125FSB



Specialty Nail — Hog Rings — Hill Pattern

Features:

- #3 pre-bent

Type 304 Stainless Steel

Gauge	Width Open (in.)	Width Across (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
13	0.812	1.57	204	S13075HR1	S13075HR5	S13075HRB
14	0.280	0.75	540	S14075HR1	—	S14075HRB



Pre-Bent Hill Pattern