

# DJT14Z

## Deck Joist Tie

The DJT14Z deck joist tie is designed to attach 2x deck joists to the side of 4x or larger support posts. The DJT14Z can be installed with either nails or bolts.


**Material:** 14 gauge

**Finish:** ZMAX® coating

**Installation:**

- Use specified HDG fasteners; see General Notes
- Recommended: install on post first
- Minimum 2x4 joist and 4x4 post

**Codes:** See p. 12 for Code Reference Key Chart



These products are available with additional corrosion protection. For more information, see pp. 13–19.

**SS** For stainless-steel fasteners, see p. 25.

**SD** Many of these products are approved for installation with Strong-Drive® SD Connector screws. See pp. 380–382 for more information.

Model No.	Fasteners (in.)			Allowable Loads				Code Ref.
	Nails	Bolts		Nails		Bolts		
		Qty.	Dia.	Floor (100)	Roof (125)	Floor (100)	Roof (125)	
<b>SS</b> DJT14Z	(8) 0.162 x 3 1/2	2	5/8	1,160	1,320	1,325	1,325	IBC, FL, LA

1. Loads are for one DJT14Z.
2. Roof loads are 125% of floor loads unless limited by other criteria. Floor loads may be adjusted for load durations according to the code provided they do not exceed those in the roof column.
3. Install bolts or nails as specified by designer. Bolt and nail values may not be combined.
4. All references to bolts are for structural-quality through bolts (not lag screws or carriage bolts) equal to or better than ASTM A307, Grade A.
5. **Fasteners:** Nail dimensions are listed diameter by length. See pp. 25–26 for fastener information.

## TA

### Staircase Angle

For use in structurally sound staircase framing. The TA eliminates costly conventional notching.

**Material:** 12 gauge


**Finish:** TA9Z/TA10Z — ZMAX coating;

TA9SS/TA10SS — stainless steel;

TA9PC/TA10PC — black powder coat (available in Spring 2026)

**Order:** May be ordered as kits with model numbers TA9ZKT and TA10ZKT. Each kit includes two ZMAX TAs and 1/4" x 1 1/2" Strong-Drive SDS Heavy-Duty Connector screws.

**Codes:** See p. 12 for Code Reference Key Chart



These products are available with additional corrosion protection. For more information, see pp. 13–19.

**SS** For stainless-steel fasteners, see p. 25.

Model No.	Fasteners		DF/SP Allowable Downloads (100)	Code Ref.
	Stringer	Tread		
<b>SS</b> TA9Z	Alt. (2) 1/4" x 1 1/2" SDS	(3) 1/4" x 1 1/2" SDS	500	—
	Typ. (3) 1/4" x 1 1/2" SDS	(2) 1/4" x 1 1/2" SDS	750	
<b>SS</b> TA10Z	Alt. (3) 1/4" x 1 1/2" SDS	(4) 1/4" x 1 1/2" SDS	750	
	Typ. (4) 1/4" x 1 1/2" SDS	(3) 1/4" x 1 1/2" SDS	1,000	

1. Loads may be adjusted for other durations according to the code.
2. **Fasteners:** SDS screws are Simpson Strong-Tie Strong-Drive SDS Heavy-Duty Connector screws. See pp. 25–26 for fastener information.

