### **Collated Exterior Screws**





# SSWSCB Roofing Tile Screw

#### **Common Applications:**


Roofing tiles to wood

#### Features:

- Bugle head
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- · Coarse threads
- Type-17 point
- Curved collation

Codes/Standards: Meets the requirements of the Tile Roofing Institute as described in ESR-2015P. A Miami-Dade compliant roofing product (2" and 21/2" only).

## Type 305 Stainless Steel



Length (in.)	Shank Size	Carton Quantity	Model No.	PRORFG2	PR0300SRFG2
13⁄4	#8	2,000	SSWSC134BS	✓	
2	#8	2,000	SSWSC2BS	✓	✓
2½	#8	1,500	SSWSC212BS	✓	✓

## WSCT Roofing Tile Screw

#### **Common Applications:**

Roofing tiles to wood

#### Features:

- Flat head
- #3 square drive (driver bit in each box; replacement bit model BIT3S)
- Twin threads
- Sharp point
- Curved collation

Codes/Standards: ASTM A641 (Class 1)

## Heavy Zinc Electroplate



Length (in.)	Shank Size	Carton Quantity	Model No.	PRORFG2	PR0300SRFG2
2½	#8	1,500	WSCT212S	✓	✓

# WSCD Roofing Tile Screw

#### **Common Applications:**

Roofing tiles to wood

#### Features:

- Flat head
- #3 square drive (driver bit in each box; replacement bit model BIT3SU)
- Twin threads
- · Sharp point
- Curved collation

Codes/Standards: Meets the requirements of the Tile Roofing Institute as described in ESR-2015P.



### Mechanically Galvanized - Class 55

Length (in.)	Shank Size	Carton Quantity	Model No.	PRORFG2	PR0300SRFG2
2½	#8	1,500	WSCD212S	✓	✓
3	#8	1,000	WSCD3S		✓