



STEDOX[®] | TEMPORARY BRACING

SUPPORT FOR MASS TIMBER CONSTRUCTION

Stedox[®] Support 23 | 6'-3"–10' | 29 lbs
(1.9–3.0 m | 13.2 kg)



Stedox[®] Support 35 | 10'–16'-4" | 40 lbs
(3.0–5.0 m | 18 kg)



Two Models

Ranging from 6'-3" to 16'-4" (3-5 m)

Lightweight Design

29 or 40 lbs (13.2 or 18 kg)

Robust Capacity

Handles loads up to 2,695 lbs (12 kN)



Stedox® End Bracket



12 x \varnothing 0.28" (7 mm) holes
Accommodates Simpson Strong-Tie®
SDS Heavy-Duty Connector Screws

2 x \varnothing 0.51" (13 mm) holes
Accommodates Simpson Strong-Tie
3/8" Dia. Titen HD® Heavy-Duty
Screw Anchors

Benefits – that Stedox® guarantees



Extra sturdy handles make adjusting the wall super easy




Easy to attach with Simpson Strong-Tie fasteners



High-clearance enables flat use as panel-puller, or to square-up light-frame panels

STRIP GALVANIZED



POWDER COATED

Double rust protection ensures a long lifetime for the wall brace



Built-in stop function makes the work safer and prevents accidents

29/40
lbs

Durable, lightweight, user-friendly: making work enjoyable and efficient



12" fine adjustment makes it easy to adjust the walls plumb



Rough adjustment is done quickly with locking pins (\approx 4" increments)



Stop-mark at the final locking position for added safety and convenience



Coated in Stedox® bright yellow paint for high visibility and safety



Alex Carney

Superintendent at Seagate Mass Timber Inc.

"They've been performing admirably so far, no complaints at all. Far superior to the other braces we were previously using."



Jason Fehlman

Owner at Carpentry Plus Inc.

"We love these braces!"

Model No.	No. of Locking Pins	Support Length		Allowable Loads	
		ft – in	mm	lbs	kN
Stedox® 23 29 lbs (13.2 kg)	1	6'–3"	1,900	1,415	6.3
		8'–2"	2,500		
		10'	3,000		
	2	6'–3"	1,900	2,695	12.0
		8'–2"	2,500		
		10'	3,000		
Stedox® 35 40 lbs (18 kg)	1	10'	3,000	1,415	6.3
		11'–6"	3,500	1,415	6.3
		13'–1"	4,000	1,415	6.3
		14'–9"	4,500	1,300	5.8
		16'–4"	5,000	1,055	4.7
	2	10'	3,000	2,695	12.0
		11'–6"	3,500	2,020	9.0
		13'–1"	4,000	1,570	7.0
		14'–9"	4,500	1,300	5.8
		16'–4"	5,000	1,055	4.7

¹⁾ Allowable loads use a factor of safety of 1.5.

²⁾ Allowable loads are the minimum of the allowable load of the brace and the allowable load of the end connection.



Stedox® temporary braces are distributed exclusively in North America by Simpson Strong-Tie.

→ For more information please visit strongtie.com/STEDOX or call (800) 999-5099

