

Metal Screws

Self-Drilling Siding Screw


Common Application:

Attach wood siding, wood panels and metal trim to steel studs

Features:

- Trim head.
- Threaded $\frac{2}{3}$ of overall length.
- #3 drill point.
- #1 square drive (replacement bit model BIT1S-2; see p. 105 for more information).
- 1 $\frac{5}{8}$ " models are fully threaded.
- Type 410 stainless steel can be hardened through heat treatment, giving it the ability to drill through metal. It does not offer the same level of corrosion resistance of either Type 316 or 305 stainless steel.
- **Warning:** Hardened stainless-steel fasteners should not be used with steel framing in environments with high humidity, condensation or other moisture that will be present at the dissimilar-metal interface.

For more information on drilling thickness capacities and drill speed recommendations, see pp. 26–27.



Type 410 Stainless Steel*

Size	Length (in.)	Threads Per Inch	Head Diameter (in.)	Approx. Count per lb.	Carton Quantity	Model No.
#7	1 $\frac{5}{8}$	19	0.23	187	100	F07T162TDC
#7	1 $\frac{5}{8}$	19	0.23	187	1,000	F07T162TDM
#7	1 $\frac{5}{8}$	19	0.23	187	5,000	F07T162TDB
#7	2 $\frac{1}{4}$	19	0.23	132	100	F07T225TDC
#7	2 $\frac{1}{4}$	19	0.23	132	1,000	F07T225TDM
#7	2 $\frac{1}{4}$	19	0.23	132	4,000	F07T225TDB
#7	3	19	0.23	105	100	F07T300TDC
#7	3	19	0.23	105	1,000	F07T300TDM
#7	3	19	0.23	105	2,000	F07T300TDB

* These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.