


Exterior Nails

Shake and Shingle Siding/Roofing Nail

Features:


- $\frac{7}{32}$ "-diameter flat head provides ample bearing surface to firmly secure shakes and shingles of all types
- Checker pattern on head blends with wood grain, reduces glare from sunlight and accepts surface finishes
- Annular ring-shank increases withdrawal resistance to provide a secure attachment
- Slender shanks minimize splitting
- Diamond point for easier driving
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance

Type 316 Stainless Steel



Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
3d	1¼	14	0.083	$\frac{7}{32}$	0.219	470	T3SN71	—	T3SN7B
4d	1½	14	0.083	$\frac{7}{32}$	0.219	394	T4SN71	T4SN75	T4SN7B
5d	1¾	14	0.083	$\frac{7}{32}$	0.219	337	T5SN71	T5SN75	T5SN7B
6d	2	13	0.092	$\frac{7}{32}$	0.219	237	T6SN71	T6SN75	T6SN7B
7d	2¼	13	0.092	$\frac{7}{32}$	0.219	216	—	T7SN75	T7SN7B
8d	2½	13	0.092	$\frac{7}{32}$	0.219	196	T8SN71	T8SN75	T8SN7B

Type 304 Stainless Steel



Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
3d	1¼	14	0.083	$\frac{7}{32}$	0.219	470	S3SN71	S3SN75	S3SN7B
4d	1½	14	0.083	$\frac{7}{32}$	0.219	394	S4SN71	S4SN75	S4SN7B
5d	1¾	14	0.083	$\frac{7}{32}$	0.219	337	S5SN71	S5SN75	S5SN7B
6d	2	13	0.092	$\frac{7}{32}$	0.219	237	S6SN71	S6SN75	S6SN7B
7d	2¼	13	0.092	$\frac{7}{32}$	0.219	216	S7SN71	S7SN75	S7SN7B
8d	2½	13	0.092	$\frac{7}{32}$	0.219	196	S8SN71	S8SN75	S8SN7B