

Interior Screws

Strong-Drive® SDCFC TIMBER-CFC SCREW

Beam Reinforcement, Wall to Wall, Floor to Floor, Support Beams, Butt Joints, Splitting Reinforcement

The Strong-Drive SDCFC Timber-CFC screw — a robust structural fastener available in a variety of long sizes (500 mm – 1,000 mm) — is designed for cross-laminated timber (CLT) construction, mass timber construction and general interior applications. These sturdy 0.390"-diameter structural fasteners provide extra strength for demanding applications requiring large-sized structural members. The compact cylinder head provides clean countersinking with a reduced footprint. The yellow zinc, fully-threaded screw, with a proprietary point, provides fast starts and excellent withdrawal resistance. For interior and dry applications only.

Features:

- Interior grade yellow zinc coating
- Compact cylinder head helps countersink the screw for an unobstructed finish
- Heavy-duty, fully-threaded 10 mm (0.390") outer diameter provides strength, with superb withdrawal resistance
- Deep 6-lobe recess for a secure drive
- Available in 500 mm (19½"), 600 mm (23½"), 800 mm (31½"), 1,000 mm (39½") lengths


For more information regarding driver bits for Simpson Strong-Tie fasteners, see p. 129.

Codes/Standards: ICC-ES ESR-3046 (including City of LA Supplement), ICC-ES ELC-3046, State of Florida FL9589

Warning: Industry studies show that hardened fasteners can experience performance problems in wet and corrosive environments. Accordingly, use this product in dry, interior and noncorrosive environments only.

For Technical Data and Loads, see C-F-2023TECHSUP *Fastening Systems Technical Guide*, p. 31

US Patent Pending



Yellow Zinc Coating

Model No.	Dimensions								Box	
	Inches				Millimeters				Packaging SKU	Fasteners per Box
	O.D. x Length	Shank Dia.	Thread Length	Head Dia.	O.D. x Length	Shank Dia.	Thread Length	Head Dia.		
SDCFC271958	0.390 x 19½"	0.290	18½"	0.525	10 x 500	7.4	467	13.4	SDCFC271958	50
SDCFC272358	0.390 x 23½"	0.290	22¼"	0.525	10 x 600	7.4	567	13.4	SDCFC272358	50
SDCFC273112	0.390 x 31½"	0.290	30½"	0.525	10 x 800	7.4	767	13.4	SDCFC273112	50
SDCFC273938	0.390 x 39½"	0.290	38"	0.525	10 x 1000	7.4	967	13.4	SDCFC273938	50

1. O.D. denotes thread outer diameter.

2. Driver bit size: T50, replacement bit part number BIT50T-2-R1.