

Collated Interior Screws

WSHL Subfloor Screw

Common Applications:

Subfloor to wood

Features:

- Ribbed flat head with nibs for easy countersinking
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- High-low threads
- Sharp point
- Gray phosphate coating
- Curved collation
- 1:1 replacement for 8d common nails when used with floor sheathing $1\frac{1}{2}$ – $2\frac{3}{32}$ " thick



Gray Phosphate Coating

Length (in.)	Shank Size	Carton Quantity	Model No.	PRO 200SG2	PRO 250G2
1 3/4	#7	2,000	WSHL134S7	✓	✓

DWC Drywall Screw


Common Applications:

Drywall to wood

Features:

- Bugle head
- #2 Phillips (driver bit in each box; replacement bit model BIT2P)
- Coarse threads
- Sharp point
- Curved collation

Codes/Standards: ASTM C1002 Type W



Gray Phosphate Coating

Length (in.)	Shank Size	Contractor Pack		PRO200G2	PRO250DWG2	PRODW
		Fasteners Per Pack	Model No.			
1	#6	2,500	DWC1PS	✓		✓
1 1/4	#6	2,500	DWC114PS	✓		✓
1 5/8	#6	2,500	DWC158PS	✓		✓
2	#6	2,000	DWC2PS	✓	✓	
2 1/2	#8	1,500	DWC212PS		✓	