

Specialty

Pancake-Head Screw


Common Applications:

Securing clips to wood used in standing-seam-roofing

Features:

- Low-profile head
- #2 square drive (replacement bit BIT2S-2; see p. 105 for more information)
- Fully-threaded shank
- Type 410 stainless steel is coated for additional corrosion protection

Type 410 stainless steel can be hardened through heat treatment, giving it the ability to drill through metal. It does not offer the same level of corrosion resistance of either Type 316 or 305 stainless steel.



Type 410 Stainless Steel*

Size	Length (in.)	Head Diameter (in.)	Carton Quantity	Model No.
#10	1	0.44	100	F10T100PTC
#10	1	0.44	1,000	F10T100PTM
#10	1	0.44	4,500	F10T100PTB
#10	2	0.44	100	F10T200PTC
#10	2	0.44	1,000	F10T200PTM

* These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.


Wire-Lath Modified Truss-Head Screw

Common Application:

Fastening lath to wood

Features:

- For use in applications where a larger bearing surface is needed underneath the head
- #2 Phillips drive
- Type-17 point



Type 305 Stainless Steel

Size	Length (in.)	Head Diameter (in.)	Carton Quantity	Model No.
#8	3/4	0.42	100	S08C075KQC
#8	3/4	0.42	1,000	S08C075KQM
#8	1 1/4	0.42	100	S08C125KQC
#8	1 1/4	0.42	1,000	S08C125KQM