Adhesive Accessories

Steel Adhesive-Anchoring Screen Tubes

Screen tubes are used in hollow base material applications to contain adhesive around the anchor and prevent it from running into voids. Simpson Strong-Tie® screen tubes are specifically designed to work with AT-XP® and ET-HP® adhesives in order to precisely control the amount of adhesive that passes through the mesh. This results in thorough coating and bonding of the rod to the screen tube and base material. Order screen tubes based upon rod diameter and adhesive type. The actual outside diameter of the screen tube is larger than the rod diameter.

Material: ATS screen tubes: 50 mesh stainless steel ETS screen tubes: 60 mesh carbon steel



Caution: Screen tubes are designed for a specific adhesive type. ETS screen tubes must be used with ET-HP formulations and ATS screen tubes must be used with AT-XP.



Screen Tube Screen tubes are for use in hollow CMU, hollow brick and unreinforced masonry applications.

Screen Tubes

For Rod Diameter (in.)	Hole Size (in.)	ATS Stainless Steel Screen Tubes for AT-XP		ETS Carbon Steel Screen Tubes for ET-HP (SET-XP® ¾" Rod Sizes)		
		Actual Screen Size 0.D./Length (in.)	Model No.	Actual Screen Size 0.D./Length (in.)	Model No.	Carton Quantity
3⁄8	9⁄16	_	_	¹⁵ ⁄32 X 6	ETS376	150
		_	_	¹⁵ ⁄32 X 10	ETS3710	100
1/2	11⁄16	—	—	¹⁹ ⁄32 X 6	ETS506	100
		_	—	¹⁹ ⁄32 X 10	ETS5010	50
5/8	7⁄8	_	_	²⁵ ⁄32 X 6	ETS626	50
		_	_	²⁵ ⁄32 x 10	ETS6210	25
			_	²⁵ ⁄32 X 13	ETS6213	25
3/4	1	³¹ / ₃₂ X 8	ATS758	³¹ / ₃₂ X 8	ETS758	25
		³¹ / ₃₂ x 13	ATS7513	³¹ / ₃₂ x 13	ETS7513	25
		³¹ / ₃₂ x 17	ATS7517	³¹ / ₃₂ x 17	ETS7517	25
		_	_	³¹ ⁄32 X 21	ETS7521	25

SIMPSO

Strong-Tie