



VENDOR#	CODE	WLL LBS	DIMENSIONS IN INCHES			WEIGHT LBS/FT	MPF kN	BREAKING FORCE LBS
			d	P	w1			
Z802300	KLA 6-10	3,306	(6MM)	0.71	0.33	0.54	8,272	13,240
Z802337	KLA 7-10	4,300	9/32"	0.83	0.39	0.74	10,790	17,309
Z802301	KLA 8-10	5,700	5/16"	0.94	0.43	0.94	14,162	22,929
Z802302	KLA 10-10	8,800	3/8"	1.18	0.55	1.55	22,030	35,518
Z802303	KLA 13-10	15,000	1/2"	1.54	0.70	2.55	37,316	60,246
Z802304	KLA 16-10	22,600	5/8"	1.89	0.86	3.77	56,424	90,369
Z802305	KLA 20-10	35,300	3/4"	2.36	1.06	6.32	88,346	141,624
Z802246	KLA 22-10	44,080	7/8"	2.60	1.14	7.93	110,376	176,468
Z802248	KLA 26-10	59,500	1"	3.07	1.38	9.81	149,267	238,737
Z802440	KLA 32-10	88,160	1-1/4"	3.78	1.64	16.40	220,528	361,928

- Short link, KL
- Heat treatment: Quenched & Tempered
- Surface treatment: Painted blue
- Note: For chain Grade 10 (200) the maximum in service temperature is 200°C.
- 4:1 Design Factor
- Fulfills the requirements in: ASTM A973/A973M-07(2012) EN 818+2:2008 (WLL +25%, reduced temperature range)